

Hvrrouterconsolidate

Contents

- [Name](#)
- [Synopsis](#)
- [Description](#)
- [Options](#)

Name

Hvrrouterconsolidate - Merge small tx files in router directory.

Synopsis

```
hvrrouterconsolidate [-options]... hubdb [chn]
```

Description

If capture jobs run without integrate jobs then many transaction files (matching `*.tx_integ/oc`) will accumulate in `$HVR_CONFIG/router/hub/chn`. These files can cause extra CPU load in other jobs. Small transaction files will also accumulate in `$HVR_CONFIG/jnl/hub/chn` if action **Integrate/JournalRouterFiles** is defined. Command **hvrrouterconsolidate** will merge many of these smaller files together.

Consolidation is unsafe while an integrate job is running; for this reason **hvrrouterconsolidate** will only consolidate router files for integrate jobs which have scheduler `job_state` as **SUSPEND** or **FAILED** or **PENDING** (unless option **-f** supplied).

If the channel name is not supplied then router consolidation will be done for all channels.

Note that consolidation will not merge all small files; the algorithm instead processes files in batches of 10, 100, 1000 etc...

The argument `hubdb` specifies the connection to the hub database. For more information about supported hub databases and the syntax for using this argument, see [Calling HVR on the Command Line](#).

Options

This section describes the options available for command **hvrrouterconsolidate**.

Parameter	Description
-b <i>base</i>	Base/radix. Otherwise 10 files are grouped.
-f	Consolidate files for all jobs, not just ones where <code>job_state</code> is inactive. Only used when the scheduler is not running.
-j	Journals only, ignore <code>/router</code> directory.
-h <i>class</i>	Location <i>class</i> of the hub database. Valid values for <i>class</i> are db2 , db2i , ingres , mysql , oracle , postgresql , sqlserver , or teradata . For more information, see Calling HVR on the Command Line .
-l <i>locscope</i>	Specific locations only. Value can have form <i>loc</i> or !/oc

-N <i>nrows</i>	Max num rows. Larger files won't be joined.
-p	Only print OS commands, no execution.
-r	Router files only, ignore /jnl directory.
-s <i>fsize</i>	No consolidate if new file would exceed <i>fsize</i> . Default is 20Mb.
-u <i>dbuser</i>	Database user name.